



**Flowmeters 6001 / 6002**

- Steel, AISI 316, PVC, PTFE, Glass tube.
- 0,1 l/h to 40 m<sup>3</sup>/h H<sub>2</sub>O.
- 20NI/h to 1.200 Nm<sup>3</sup>/h air.
- Accuracy class: 1,6.
- 1 or 2 limit switches.



**Flowmeters PT11 / PT12**

- Tube in Trogamid or Polysulfon.
- 10 l/h to 40 m<sup>3</sup>/h H<sub>2</sub>O.
- 160 NI/h to 1.200 Nm<sup>3</sup>/h air.
- Accuracy class: 4.
- 1 or 2 limit switches.



**Flowmeters serie 2000**

- AISI 316.
- 0,1 l/h to 1.000 l/h H<sub>2</sub>O.
- 10 N/h to 17 Nm<sup>3</sup>/h air.
- Accuracy class: 1,6 to 6.
- Precision regulating valve or flow regulator.
- 1 or 2 limit switches.



**FLOMID, Magnetic Inductive Flowmeters**

- PTFE, EBONITA, PF, PVDF.
- Electrodes AISI 316, Hastelloy, Zr, Titanium.
- DN 10 to DN 500.
- 10/h to 6.000 m<sup>3</sup>/h H<sub>2</sub>O.
- Accuracy: ± 0,75%
- 0...4-20 mA.
- 0...1.000 Hz.



**DP 65 / DP 500  
Target Flowmeters**

- Steel with polyamid covered, AISI 316, Hastelloy.
- 2 m<sup>3</sup>/h to 1.600 m<sup>3</sup>/h H<sub>2</sub>O.
- Accuracy class: (2,5) DP65 (4) DP500.
- 0...4-20 mA
- 3 to 15 psi.
- Counter LCD.
- 1 or 2 limit switches.



**Orifice Plate PR**

- Steel with polyamid covered, AISI 316, PVC, PTFE.
- 2 m<sup>3</sup>/h to 20.000 m<sup>3</sup>/h H<sub>2</sub>O.
- 30 Nm<sup>3</sup>/h to 300.000 Nm<sup>3</sup>/h air.
- Accuracy class: 4.
- 0...4-20 mA.
- 1 or 2 limit switches.



**Metal - Tube Flowmeters  
SC 250**

- AISI 316, Hastelloy, PVC, PTFE.
- 2,5 l/h to 180 m<sup>3</sup>/h H<sub>2</sub>O.
- 70 N/h to 5.400 Nm<sup>3</sup>/h air.
- Accuracy class: 2,5 or 1,6.
- 0...4-20 mA
- 3 to 15 psi.
- Counter LCD.
- 1 or 2 limit switches.



**Flowmeters M-21**

- AISI 316, Hastelloy.
- 0,1 l/h to 1 m<sup>3</sup>/h H<sub>2</sub>O.
- 30 NI/h to 30 Nm<sup>3</sup>/h air.
- Accuracy class: 4.
- 0...4-20 mA.
- 1 or 2 limit switches.



### TM-44 Turbine Flowmeters

- AISI 316, AISI 420.
- DN 10 to DN 500.
- 100 l/h to 8.000 m<sup>3</sup>/h H<sub>2</sub>O.
- 3.000 NI/h to 300.000 Nm<sup>3</sup>/h air.
- Accuracy: ± 0,5%
- 0...4-20 mA with electronic MC 01 or MT 02.



### FLOMAT, Electromagnetic Insertion Flowmeters

- PTFE, PVC, PVDF.
- Electrodes AISI 316, Hastelloy, Zr, Titanium.
- DN 10 to DN 500.
- 10/h to 6.000 m<sup>3</sup>/h H<sub>2</sub>O.
- Accuracy: ± 3,5%
- 0...4-20 mA.
- 0...10.000 Hz.



### Volumetric Counter COVOL

- AISI 316, PPH, PTFE.
- DN 10 to DN 100.
- 10 l/h to 60 m<sup>3</sup>/h H<sub>2</sub>O.
- Viscosity values up to 120.000 m Pa.s.
- Accuracy: ± 0,8%
- 0...4-20 mA with electronic MC-01 or MT-02.



### Electronic MC 01

- 96 X 96.
- Flow rate indication totalisation the set batching, traducer.
- 0...4-20 mA.



### Level indicator LP 80

- AISI 316, PVC, PTFE.
- Top mounted.
- 0,3 m to 6 m.
- Accuracy: ± 1,5...2 mm.
- 1 or 2 limit switches.
- 0...4-20 mA.
- 3-15 psi.



### Level indicator LT-10

- AISI 316, PVC, PTFE, PVDF.
- Side mounted.
- 0,3 m to 15 m.
- Accuracy: ± 3...4 mm.
- Limit switches adjustable.
- 0...4-20 mA.



### Level controller float LC 30

- AISI 316, PVC, PTFE, PP.
- Top mounted.
- 1 to 9 limit switches.
- 0...4-20 mA.

### Level controller float LC 40

- AISI 316, PVC, PTFE, PP.
- Side mounted.
- 1 or 2 limit switches.
- ADF execution.



### Level switch LD 60

- AISI 316 L, PVC, PTFE.
- Hastelloy C
- DN 10 to DN 500.
- -30° C + -115° C.
- Histéresis: ± 2 mm.H<sub>2</sub>O
- IP 65 DIN.
- 16 bar.